

RELEASE INFORMATION FULL CAST TURBO OUTLET PIPE FOR RB26DETT



The stock turbo outlet tends to build up too much secondary back pressure due to its restrictive capacity. The new design is capable of supporting even higher flow compared to the whole design and removing the intake / compressor housing relieves.

Designed from scratch for the best flowing efficiency.



SPEC

	TOMEI		STD			
	SUS316 Full Cast		BNR32 / BCNR33		BNR34	
MATERIAL	SUS316		Casted Steel		Pressed & Welded	
	Fr	Re	BCNR33 Fr	BCNR33 Re	BNR34 Fr	BNR34 Re
WEIGHT	1.85kg	2.10kg	2.3kg	2.7kg	1.75kg	1.9kg
CAPACITY	800cc	900cc	630cc	730cc	600cc	725cc
EXIT DIA.	Approx. φ66		Approx. φ58		Approx. φ55	
PIPE THK.	Approx. t=2.8		Approx. t=4.5		Approx. t=2	
FLANGE THK.	Approx. t=11		t=11 ~ 14		t=11.6	

*Numbers may slightly differ due to manual measuremen



Wide mouth design



Step-less connection with a 70mm front pipe.



Updated to the same finish as the Tomei Full Cast Exhaust Manifold (sold separately) for a matching and better appearance.

APPLICATION: BNR32/BCNR33/BNR34

JPY 95,000

RELATED PRODUCT Incredibly durable and reliable!



FULL CAST EXHAUST MANIFOLD

- Made of SUS316, full lost-wax casted structure.
- Superior performance and exhaust note at all range. Smooth merging angles minimize exhaust interference.
- Designed to maximize flowing efficiency.
- Precisely detailed, elaborate finish.
- Durable does not necessarily mean heavy.

APPLICATION: BNR32.BCNR33. BNR34

Turbo compatibility:

Nissan STD, Nissan STD N1, Any Bolt-On Turbo

JPY 128,000

TOMEI POWERED INC.