

# TOMEI Camshaft Spec Card

PART NAME **PROCAM** ENGINE **RB26DETT BNR32/BCNR33**

PART NUMBER **SET** - **IN** 1421280108 **EX** 1422280108

※BNR32/BCNR33/BNR34 compatible

GRIND	IN	280° / 10.80mm	SOLID	BACE	IN	Φ30.0	ROCKER ARM RATIO*	VALVE CLEARANCE	IN	0.45
	EX	280° / 10.80mm	SOLID	CIRCLE(Φ)	EX	Φ30.0	-	WHEN COLD	EX	0.38

LIFT	IN	@CAM 10.80mm	@VALVE 10.35mm	LOBE	IN	110.0
	EX	@CAM 10.80mm	@VALVE 10.42mm	CENTER(°)	EX	115.0

\* ALL LIFTS ARE BASED ON ZERO LASH AND THORETICAL ROCKER ARM RATIOS

CAM TIMING		OPENS(°)	CLOSES(°)	Actual Duration @ Opening (°)
Actual Duration	IN	BTDC 30.0	ABDC 70.0	280.0
Valve Lift	EX	BBDC 75.0	ATDC 25.0	280.0





Values shown are, from start to the end of actual duration. (Excluding the ramp values)

CAM TIMING		OPENS(°)	CLOSES(°)	TOTAL DURATION(°)
at 1mm	IN	BTDC 13.0	ABDC 50.0	243.0
Valve Lift	EX	BBDC 58.0	ATDC 8.0	246.0

Values are of actual duration from start to end of 1mm value points. (Excluding ramp values)

CAM TIMING		OPENS(°)	CLOSES(°)	TOTAL DURATION(°)
at 0.05"	IN	BTDC 11.0	ABDC 48.0	239.0
Valve Lift	EX	BBDC 56.0	ATDC 6.0	242.0

Values are of actual duration from start to end of 0.05" value points. (Excluding ramp values)



REQUIRED VALVE SPRING SPEC	
NOMAL HEIGHT (mm)	45.0
SET LENGTH (mm)	40.2
LIFT LENGTH (mm)	29.0
COMPRESSED HEIGHT(mm)	28.0
SET LOAD (kgf)	24.0 ± 7%
LIFT LOAD (kgf)	97.8 ± 7%
TOMEI PART NUMBER	173002

REQUIRED PARTS	
PRODUCT NAME	TOMEI PART NUMBER
VALVE LIFTER	163005
MODIFICATION FOR BIGGER CAM	31101010
ADJUSTABLE CAM PULLEYS IN	152009
ADJUSTABLE CAM PULLEYS EX	152010
VALVE RECESSION 4VALVES	32109040

**TOMEI**  
The Engine Specialist