

# FORGED PISTON for RB25DET



## Compatible With The Stock Engine!

The  $\varphi$ 86.5 size piston suitable for overhaul has been newly added to the RB25DET piston series. Piston profile the ellipse barrel shape profile was chosen from the advanced analysis of the analysis distribution of piston temperatures, material properties and the coefficient thermal expansion rates. This allowed our design to use much tighter piston clearances for maximum power range. This greatly reduces blow by gases, friction loss and no noise.

	Bore (mm)	Pin Dia. (mm)	Length (mm)		Comp.Height (mm)	PistonCrown Volume (cc)	Top ring B×T (mm)	Second ring B×T (mm)	Oil ring B×T (mm)	Displacement (cc)
ECR33	86.5	21	60	×	31.0	-12.7				
NEO6 (ER34,WGNC34,C35)	86.5	21	60	0	30.0	-7.8	1.20×3.10	1.20×3.90	2.50×3.10	2527

### JPY165,000

For ECR33 P/N:1113865111

For NEO6 P/N: 1114865112

### **RELATED PRODUCT**

### HEAD GASKET



APPLICATION	BORE(Φ)	THICKNESS	P/N
		1.2mm	1312870121
	87.0	1.5mm	1312870151
RB25DE(T)		1.8mm	1312870181
	88.0	1.2mm	11044R904G
	00.0	1.5mm	11044R905G

#### Sample Compression Ratio

APPLICATION	BORE		Gasket			
APPLICATION	DURE	1.2mm	1.5mm	1.8mm	BORE	
ECR33	φ 86.5	8.4	8.2	8.0	φ87.0	
		8.4	8.2	7.9	φ88.0	
NEO6		9.1	8.8	-	φ87.0	
		9.1	8.8	-	φ 88.0	

#### ■ SUPER GROMMET DESIGN



The SUPER GROMMET is dual sealing method of the bead structure & metal grommet, provides maximum sealing for the coolant, oil & gases around the bore circumference.

### ■ Heat Conductivity & The Strength of Stainless Steel

Stainless steel was chosen to be the material of choice to make the Metal Gaskets with because of the heat conductivity efficiency of the stainless steel material to evenly distribute the heat and aid with cooling. This will greatly improve reliability and reduce the chances of problems.

JPY 28.000

### TOMEI POWERED INC.